

Influence of pre-existing volcanic edifice geometry on caldera formation

Virginie Pinel

To cite this version:

Virginie Pinel. Influence of pre-existing volcanic edifice geometry on caldera formation. Geophysical Research Letters, 2011, 38, pp.L11305. 10.1029/2011gl047900. ird-00618258

HAL Id: ird-00618258 <https://ird.hal.science/ird-00618258v1>

Submitted on 1 Sep 2011

HAL is a multi-disciplinary open access archive for the deposit and dissemination of scientific research documents, whether they are published or not. The documents may come from teaching and research institutions in France or abroad, or from public or private research centers.

L'archive ouverte pluridisciplinaire **HAL**, est destinée au dépôt et à la diffusion de documents scientifiques de niveau recherche, publiés ou non, émanant des établissements d'enseignement et de recherche français ou étrangers, des laboratoires publics ou privés.

¹ Influence of pre-existing volcanic edifice geometry on

Journal of Geophysical Research, vol. \mathcal{E} , \mathcal{E}

² caldera formation

V. Pinel, 1

V. Pinel, ISTerre, IRD R219, CNRS Université de Savoie, Campus Scientifique, 73376 Le Bourget du Lac Cedex, France (Virginie.Pinel@univ-savoie.fr)

 1 ISTerre, IRD R219, CNRS Université de Savoie, Campus Scientifique, 73376 Le Bourget du Lac Cedex, France

³ **Abstract.** Volcanic edifice construction at the Earth's surface significantly modifies the stress field within the underlying crust with two main implica- tions for caldera formation. First, tensile rupture at the Earth's surface is favored at the periphery, which enables ring fault formation. Second, edifice formation amplifies the amount of pressure decrease occurring within a magma reservoir before the eruption stops. Taking into account both of these effects, caldera formation can be initiated during a central eruption of a pre-existing volcano even when assuming elastic behaviour for the surrounding crust. Pro- viding the roof aspect ratio is small enough, conditions for caldera forma- $_{12}$ tion by reservoir withdrawal can be reached whatever the reservoir shape is. ¹³ However ring fault initiation is easier for laterally elongated reservoirs.

1. Introduction

¹⁴ Many caldera-forming deposits record energetic eruptive phases prior to the "syncol-¹⁵ lapse" deposits characterized by ignimbrites, which is consistent with an onset of caldera ¹⁶ occurring during an ongoing eruption that is to say when the magma reservoir pressure 17 is decreasing by withdrawal [*Marti et al.*, 2008]. Based on this field observation as well as ¹⁸ experimental and mathematical modelling, *Marti et al.* [2009] define two types of caldera ₁₉ depending on the pressure evolution within the magmatic reservoir leading to ring faults ²⁰ formation and caldera-forming eruption. One caldera type is formed by magma pressure ²¹ increase within a sill-like magma reservoir in the presence of a regional extensive field α [Gudmundsson, 1998] and starts with the eruption. The other caldera type is formed by ²³ magma pressure decrease during an ongoing eruption. Based on the compilation of in-²⁴ formation gathered in the Collapse Caldera Data Base (CCDB), Geyer and Marti [2008] ²⁵ show that the second type that occurs during reservoir withdrawal is, by far, the most ²⁶ common.

₂₇ In the case of caldera formation induced by reservoir withdrawal, the key question to ²⁸ address, concerns the amount of depressurization that a given reservoir can reach and ²⁹ whether or not this depressurization is sufficient to ensure ring fault formation. Consid-³⁰ ering the crustal surrounding medium as elastic, reservoir depressurization is limited by ³¹ dyke closure at the reservoir wall [*McLeod and Tait*, 1999; *Marti et al.*, 2008]. However, ³² except for a few recent studies [Geyer et al., 2006; Folch and Marti, 2009], most of the-33 oretical work based on fluid dynamics [Druitt and Sparks, 1984], as well as analogical μ_{34} [Roche et al., 2000] and numerical studies [Folch and Marti, 2004] ignore this problem

³⁵ and do not discuss whether or not conditions for ring fault initiation are compatible with ³⁶ realistic pressure conditions within the reservoir. Besides, most authors favoring caldera ³⁷ formation by reservoir withdrawal consider that the crust has to behave non-elastically 38 [*Marti et al.*, 2008].

³⁹ The fact that caldera characteristics are linked to the pre-existing volcanic edifice ge-⁴⁰ ometry has long been recognised [*Wood*, 1984]. More recently, based on the compilation ⁴¹ of information gathered in the Collapse Caldera Data Base (CCDB), Geyer and Marti $_{42}$ [2008] showed that, in most cases (53, 3%) pre-caldera volcanic activity involves the devel-⁴³ opment of long lived stratovolcanoes or stratocones and that another significant amount $_{44}$ (11%) of calderas are formed on pre-existing shield volcanoes. It is known that eruptive ⁴⁵ products accumulation at the Earth's surface and edifice formation significantly modifies ⁴⁶ the underlying stress field within the crust with consequences for the magma plumbing $_{47}$ system development *[Pinel and Jaupart*, 2003]. However only a few studies dealing with ⁴⁸ caldera formation take into account the edifice's potential influence [Walter and Troll, $_{49}$ 2001; Lavallée et al., 2004; Pinel and Jaupart, 2005].

⁵⁰ In this study, numerical simulations in axisymmetric geometry are performed in order ⁵¹ to determine under which conditions a caldera formation might occur when considering ⁵² a realistic range of pressure within the magma reservoir and a volcanic edifice at the ⁵³ Earth's surface. The model is developed following the framework proposed by *Pinel and* $_{54}$ Jaupart [2005] who performed an analytical study in 2D (plane strain approximation) for ⁵⁵ cylindrical magma reservoirs. In this new paper, the influence of the roof aspect ratio ⁵⁶ (reservoir depth/reservoir lateral extension), the reservoir size as well as the edifice slope

⁵⁷ are discussed, and a primary additional contribution is to investigate the influence of the ⁵⁸ reservoir shape (ellipticity).

2. Model description

2.1. Geometry and general settings

⁵⁹ An ellipsoidal magma reservoir filled with liquid magma embedded in an homogeneous ⁶⁰ elastic medium (rigidity G and Poisson's ratio ν) is considered (see Fig 1 a). The magma α density is assumed equal to the density (ρ) of the surrounding crust and the state of 62 reference is lithostatic $(σ_{rr} = σ_{zz} = σ_{θθ} = -\rho gz > 0$ with $-z$, the depth). Departure ⁶³ from this lithostatic state of reference is induced by either a differential magma pressure ⁶⁴ ($\Delta P > 0$ for an overpressurized reservoir and $\Delta P < 0$ for an underpressurized reservoir) ⁶⁵ or the presence of an edifice at the Earth's surface, whose geometry is characterized by its ⁶⁶ radius R_v and slope α . The magma reservoir geometry is characterized by its horizontal σ semi-axis a, its vertical semi-axis b and its roof depth H. A key parameter is the reservoir ⁶⁸ ellipticity (e) defined by the ratio $e = a/b$, ellipticity being equal to 1 for the spherical ⁶⁹ case, smaller than 1 for vertically elongated reservoirs (prolate) and larger than 1 for η horizontally elongated reservoirs (oblate). The maximum value of the semi-axis will be ⁷¹ referred to as L_c ($L_c = a$ for oblate shapes and $L_c = b$ for prolate ones). Another key α parameter when studying calderas is the roof aspect ratio (R) defined as the ratio of the ⁷³ reservoir roof thickness over its width $(R = H/(2a))$ [Roche et al., 2000; Geyer et al., $74 \quad 2006$].

⁷⁵ Stress and strain within the crust are numerically calculated solving the equations for ⁷⁶ linear elasticity with the "Finite Element Method" (COMSOL software). The domain of π calculation is a 100^{*}100 km square box with a mesh of about 100 000 triangular units that

⁷⁸ is refined around the volcanic edifice and magma reservoir. No displacement perpendicular σ_{ν} to the boundary is allowed at the bottom and lateral boundaries, the upper boundary is ⁸⁰ considered as a free surface. The edifice is modelled with a normal stress applied at ⁸¹ the upper surface $(\sigma_n = \rho_m g \alpha R_v (1 - r/R_v)$ for $r < R_v$ and a normal stress equal to ⁸² the magma overpressure is applied at the reservoir walls. Numerical solutions have been ⁸³ validated using well-known analytical solutions as detailled in *Albino et al.* [2010]. Figure ⁸⁴ 1b shows that the edifice load at the surface tends to induce, respectively, compression in ⁸⁵ the central part, and tension at the periphery, the tensile effect having a smaller amplitude. ⁸⁶ An underpressurized reservoir has roughly the same effect (Fig. 1c) whereas the effect of ⁸⁷ an overpressurized reservoir (Fig. 1d) is opposite (large tensile stress in the central part ⁸⁸ and comparatively small compressive stress at the periphery).

2.2. Condition for caldera formation

⁸⁹ Most numerical studies consider that the main criterion required for caldera formation ⁹⁰ is that tensile failure can occur at the Earth's surface at some lateral distance from the ⁹¹ axis in order to produce ring faults [Gudmundsson et al., 1997; Folch and Marti, 2004; α Pinel and Jaupart, 2005. It is also often required for the rupture location to be above ⁹³ the maximum lateral extension of the underlying magma reservoir [Folch and Marti, ⁹⁴ 2004; Kinvig et al., 2009] to ensure the mechanical behaviour of the ring fault linking the ⁹⁵ Earth's surface to the reservoir walls and to reproduce field observations. For a detailled ⁹⁶ description of conditions required for ring faults formation see Folch and Marti [2004]; γ Kinvig et al. [2009]; Geyer and Binderman [2011].

⁹⁸ Here, the criterion considered for caldera formation only requires that tensile failure of ⁹⁹ the Earth's surface occurs at some distance from the axis. However the position of this

¹⁰⁰ rupture with regards to the reservoir walls is discussed later.

¹⁰¹ Tensile failure of the Earth's surface periphery should be favored by the edifice load (Fig. ¹⁰² 1b) and the reservoir depressurization (Fig. 1c). The tensile failure criterion given by ¹⁰³ Pinel and Jaupart [2005] is generalised here in the three-dimensions, in order to calculate ¹⁰⁴ the magma pressure required within the reservoir for roof breakdown. It follows that 105 tensile rupture occurs when $[2\sigma_{rr}(r, z = 0) - \sigma_{zz}(r, z = 0) - \sigma_{\theta\theta}(r, z = 0)]/3 = -T_s$, 106 where σ_{rr} , σ_{zz} and $\sigma_{\theta\theta}$ are the three principal components of the stress tensor at the 107 Earth's surface expressed in the cylindrical coordinate system, and T_s is the rock tensile ¹⁰⁸ strength. Due to the tensile effect, respectively, induced by an overpressurized reservoir in ¹⁰⁹ the central part (see Figure 1 d), and an underpressurized reservoir at the periphery (see $_{110}$ Figure 1 c), tensile rupture induced by reservoir inflation only occurs at the axis (r=0) ¹¹¹ and cannot account for ring fault formation. Earth's surface rupture at the periphery is ¹¹² thus the consequence of reservoir pressure decrease (reservoir deflation) below a threshold 113 value (ΔP_{crit}) , such that the above equation is verified.

2.3. Realistic pressure range within the reservoir

 Magma pressure within a reservoir might increase by replenishment and/or by volatiles ¹¹⁵ exsolution due to magma crystallisation [*Tait et al.*, 1989]. However this increase is lim- ited by the rupture of the reservoir walls leading to magma propagation away from the reservoir. Failure of the reservoir wall occurs when the deviatoric stress component, at 118 the walls, reaches the tensile strength $Tait$ *et al.*, 1989; *Pinel and Jaupart*, 2003]. When magma leaves the reservoir, it induces a pressure decrease within the storage zone. Con- sidering an elastic behaviour of the crust, this pressure decrease is also limited. When the magma pressure fails below the normal pressure applied at the dyke walls, the dykes get

 closed. Conditions for the cessation of magma withdrawal define a lower bound for the 123 reservoir pressure noted ΔP_{min} . One must assess whether or not the pressure decrease within the magma reservoir can be sufficient to induce ring fault formation, that is to say that we have to specify conditions under which one may have $\Delta P_{min} < \Delta P_{crit}$.

3. Results

 Figure 2 shows, for various reservoir ellipticities, the edifice size required for caldera 127 formation (to have $\Delta P_{min} < \Delta P_{crit}$). Within the framework of this particular model, which considers an initial lithostatic stress field, ring fault formation is not expected, when no edifice is present at the Earth's surface, whatever the reservoir shape is. The ¹³⁰ edifice growth at the surface always acts to favor tensile rupture at the periphery and, in ¹³¹ most case, enables the reservoir to becomes underpressurized $(\Delta P_{min} < 0)$ [Pinel et al., 2010]. Both effects tend to favor ring faults formation. In the case of a roof aspect ratio equal to 1, caldera formation can only occur for horizontally elongated reservoirs, whereas, when the roof aspect ratio is equal to 0.25, caldera formation might occur whatever the reservoir shape is, the edifice size required being larger for prolate reservoirs. Results 136 previously obtained in 2D by Pinel and Jaupart $[2005]$ are similar to this paper's new $_{137}$ results in 3D when considering a spherical shape, except for a small reservoir (Fig. 2 a), for which ring fault initiation appears more difficult in 2D. Figure 2 also shows that the fault linking the Earth's surface rupture to the reservoir wall is nearly vertical only for small roof aspect ratios. For a given reservoir ellipticity, the edifice size required for caldera formation usually increases with the roof aspect ratio. For a strato-volcano characterized by a slope of 30 degrees, the maximum roof aspect ratio allowing caldera formation is close to 1 and I checked that this maximum value does not evolve when considering larger

ellipticities.

 In order to interpret field observations, it might be useful to compare the caldera and edifice predicted sizes. Figure 3 shows that, in general, the caldera is smaller than the pre- existing edifice (caldera/edifice radius smaller than 1). The amount of the edifice surface affected by the caldera collapse increases with the magma reservoir size (larger values of caldera/edifice radius for plain curves than for dotted ones). Another observation is that ¹⁵⁰ the caldera accounts for a larger fraction of the edifice in stratovolcanoes ($\alpha > 0.3$, Fig $_{151}$ 3a,b) than in shield volcanoes ($\alpha \approx 0.1$, Fig 3c), which is consistent with field observations $152 \quad [Wood, 1984]$. The caldera versus edifice ratio can bring additional constraints on the magma reservoir shape and size. Information on caldera geometry is available in most cases from the CCDB whereas the volcanic edifice size can be inferred from the topography provided by the SRTM Digital Elevation Model. In a few cases, the CCBD also provides an estimation of the roof aspect ratio. Such data have been reported for seven volcanoes to Figure 3. For instance, Crater Lake caldera formed on Mount Mazama, 6845 yr ago, is characterized by an edifice slope close to 0.3, a caldera versus edifice radius of 0.4 [Pinel $_{159}$ and Jaupart, 2005 and a roof aspect ratio between 0.5 and 1. From Figure 3 b), this geometry is consistent with a 4 km radius spherical reservoir or a smaller reservoir (2.5 km $_{161}$ radius) as previously proposed by *Pinel and Jaupart* [2005] but having a laterally elongated shape. Vesuvius is characterized by a slighly larger caldera/edifice radius (around 0.5) as well as a slighly larger roof aspect ratio (between 0.6 and 1.2), which is consistent with a 4km radius laterally elongated reservoir. An oblate shape is thus required for the ¹⁶⁵ magma reservoir at Vesuvius, as previously proposed by *Pinel and Jaupart* [2005]. From Figure 3 c) the formation of Medecine Lake or Newberry calderas, on pre-existing shield

 volcanoes could be explained by the presence of a very shallow reservoir of radius 2.5 km or a slightly larger and deeper one (radius around 4km), whereas the formation of Opala, Ksudach and Krashennikov calderas in Kamchatka can only be explained by shallow and ¹⁷⁰ large spherical reservoirs $(L_c \geq 4km)$.

4. Discussion and Conclusion

 In order to explain caldera formation by magma withdrawal, *Marti et al.* [2008] con-¹⁷² sider that the reservoir wall behaviour departs from elasticity. Some phenomena such as conduit wall erosion could eventually prevent dyke from closure. However erosion of the central conduit by respectively, abrasion or fluid shear stress, is mainly restricted to a $_{175}$ limited portion, respectively, above or around, the fragmentation level [*Macedonio et al.*, $_{176}$ 1994, which is supposed to be located within the upper 1 km of the conduit [*Massol and* Koyaquchi, 2005. It follows that, in most cases, it seems realistic to neglect conduit wall erosion at the magma reservoir level, before ring faults formation. The main conclusion of the present study is that caldera formation by reservoir withdrawal (that is to say, pressure decrease) can occur even considering an elastic behaviour for the surrounding crust. However, in order to further discuss the potential effects of previous events, lateral variations of the physical properties of the crust should be taken into account.

¹⁸³ This study based on an elastic model only allows discussion of the initiation of caldera 184 formation that is to say the onset of medium fracturation. It does not bring any insight into ¹⁸⁵ the further development of the caldera and the way the initial fracture propagates, which ¹⁸⁶ would require analog modelling [Roche et al., 2000] or the use of numerical modelling based ¹⁸⁷ on the Discrete Element Method (DEM) [Hardy, 2008; Holohan et al., 2009]. Once the

 caldera formation has started the crustal behaviour can obviously no longer be considered as elastic.

 This work only considers caldera formation associated with a summit eruption. Some caldera formations, mainly in the case of basaltic volcanoes, are caused by lateral eruptions ¹⁹² or magma intrusions [*Michon et al.*, 2011]. Lateral magma propagation as well as often associated large flank displacements, indicate an extensional regime within the edifice. It follows that the model presented here, which relies on the assumption of an initial lithostatic stress field, is not appropriated to discuss such cases.

 This study shows that the building of a volcanic edifice by accumulation of eruptive products at the Earth's surface favors caldera formation by inducing tensile stress at the Earth's surface and enabling larger depressurization within the magma reservoir. This $\frac{1}{199}$ conclusion was already supported by an earlier analytical study $[Pinel and Jaupart, 2005]$ however it is, here, generalised for the 3-dimensional case and various reservoir shapes. Conditions for coherent caldera formation are easier to achieve in the case of small roof ₂₀₂ aspect ratios, as shown by *Roche et al.* [2000]; *Pinel and Jaupart* [2005]; *Geyer et al.* [2006]. For larger roof aspect ratios, larger edifice size are required to induce caldera formation. Caldera collapse can even affect vertically elongated reservoirs provided that the roof aspect ratio remains small. However horizontally elongated reservoir are much more favorable. With this particular geometry, caldera formation might occur for larger roof aspect ratios. The present model considering an initial lithostatic stress field cannot explain caldera formation in the case where there is no pre-existing edifice at the Earth's surface (which represents less than 15% of the documented calderas as reported by the ²¹⁰ CCDB Geyer and Marti [2008]) or if the roof aspect ratio is larger than 1 for stratovol-

₂₁₁ canoes or larger than 1.3 for shield volcanoes (which represents a few documented cases, for example Ceburoco, as reported by the CCDB). It can also not explain ring fault ini- tiation by reservoir inflation. However the initial stress field could be, in many cases, different from the lithostatic one and most calderas are formed in extensional tectonic regime (which is the case for Ceboruco). The effect of an extensional regime should favor caldera formation and could be easily quantified with the framework used in this study. ²¹⁷ The model presented here predicts that the caldera size versus the edifice one should be smaller in case of shield volcanoes than for strato-volcanoes, which is consistent with ob- $_{219}$ servations [Wood, 1984]. It also places some constraints on the magma reservoir geometry based on surface observations.

 Acknowledgments. The author thanks F. Albino for his help with numerical mod-elling development, J. Marti and A. Geyer for providing helpful comments.

References

- Albino, F. and Pinel, V. and Sigmundsson, F. (2010),Influence of surface load variations $_{224}$ on eruption likelihood: Application to two Icelandic subglacial volcanoes, Grimsvötn 225 and Katla, *Geophys. J. Int.*, $181, 1.510-1.524$.
- Druitt, T. H., and R. S. J. Sparks (1984), On the formation of calderas during ignimbrite ²²⁷ eruptions, *Nature*, 310, 679–681.
- Folch, A., and J. Marti (2004), Geometrical and mechanical constraints on the formation
- of ring-fault calderas, Earth Planet. Sci. Lett., 221, 215–225.
- Folch, A., and J. Marti (2009), Time-dependent chamber and vent conditions during ₂₃₁ explosive caldera-forming eruptions, *Earth Planet. Sci. Lett.*, 280, 246–253.

- ²³² Geyer, A., and J. Marti (2008), The new worldwide collapse caldera database (ccdb): A ₂₃₃ tool for studying and understanding caldera processes, *J. Volcanol. Geotherm. Res.*, $175, 334 - 354.$
- ²³⁵ Geyer, A., A. Folch, and J. Marti (2006), Relationship between caldera collapse and ²³⁶ magma chamber withdrawal: an experimental approach, *J. Volcanol. Geotherm. Res.*, $_{237}$ 157, 375–386.
- ²³⁸ Geyer, A., I. Binderman, Glacial influence on caldera-forming eruptions, J. Volcanol. ²³⁹ Geotherm. Res., in press.
- ²⁴⁰ Gudmundsson, A. (1998), Formation and development of normal-fault calderas and the $_{241}$ initiation of large explosive eruptions, *Bull. Volcanol.*, 60, 160–170.
- ²⁴² Gudmundsson, A., J. Marti, and E. Turon (1997), Stress fields generating ring faults in $\frac{243}{4}$ volcanoes, *Geophysical Research Letters*, 24, 1,559–1,562.
- ²⁴⁴ Hardy, S. (2008), Structural evolution of calderas: Insights from two-dimensional discrete ²⁴⁵ element simulations, *Geology*, 36 , $927-930$.
- $_{246}$ Holohan, E. P., M. P. Schöpfer, and J. J. Walsh (2009), Pit Craters and Collapse Calderas:
- ²⁴⁷ Structural Influences of Initial Mechanical and Geometric Properties as revealed by 2D
- ²⁴⁸ Distinct Element Method (DEM) Models, *Eos. Trans. AGU*, 90.
- ²⁴⁹ Kinvig, H. S., A. Geyer, and J. Gottsmann (2009), On the effect of crustal layering on
- ₂₅₀ ring-fault initiation and the formation of collapse calderas, J. Volcanol. Geotherm. Res., $186, 293 - 304.$
- $_{252}$ Lavallée, Y., J. Stix, B. Kennedy, M. Richer, and M.-A. Longpré (2004), Caldera subsi-
- ²⁵³ dence in areas of variable topographic relief: results from analogue modeling, J. Vol-
- ²⁵⁴ canol. Geotherm. Res., 129, 219–236, doi:10.1016/S0317-0273(03)00241-5.

- ²⁷⁸ doi:10.1016/j.jvolgeores.2010.05.006.
- ²⁷⁹ Roche, O., T. H. Druitt, and O. Merle (2000), Experimental study of caldera formation, ²⁸⁰ J. Geophys. Res., 105, 395–416.
- ²⁸¹ Tait, S., C. Jaupart, and S. Vergniolle (1989), Pressure, gaz content and eruption period-
- ²⁸² icity of a shallow, crystallising magma chamber, *Earth Planet. Sci. Lett.*, 92, 107–123.
- ²⁸³ Walter, T. R., and V. R. Troll (2001), Formation of caldera periphery faults: an experi-
- $_{284}$ mental study, *Bull. Volcanol.*, 63, 191–203.
- 285 Wood, C. A. (1984), Calderas: a planetary perspective, *J. Geophys. Res.*, $89, 8,391-8,406$.

Figure 1. Model geometry and stress field induced at the Earth's surface. a) Model geometry and key parameters. b) Radial stress $(\sigma_{rr}(r))$ induced at the Earth's surface by an edifice load (radius $R_v = 2$ km) when the magma reservoir is at lithostatic equilibrium ($\Delta P = 0$). The stress is normalised by the load applied at the axis. c) Radial stress $(\sigma_{rr}(r))$ induced at the Earth's surface by an underpressurized magma reservoir $(\Delta P < 0)$ with no edifice at the surface. The stress is normalised by the magma reservoir underpressure ($|\Delta P|$). d) Radial stress $(\sigma_{rr}(r))$ induced at the Earth's surface by an overpressurized magma reservoir $(\Delta P > 0)$ with no edifice at the surface. The stress is normalised by the magma reservoir overpressure (ΔP) . Radial stress calculations are obtained for a reservoir depth H of 0.5 km and maximum extension L_c of 0.5 km. Poisson's ratio is equal to 0.25. The black, blue and red curves are obtained, respectively, for a reservoir ellipticity (e) of 0.5, 1 and 2. The grey area corresponds to tensile stress (negative values).

Figure 2. Edifice size required for caldera formation as a function of the roof aspect ratio. The edifice considered is a strato-volcano of slope $\alpha = 0.6$, maximum radius of 10 km and a density of 2800 kgm[−]³ . Poisson's ratio is equal to 0.25 and the rock tensile strength is equal to 200 bars. Results are presented for various reservoir sizes: a) Maximum reservoir extension L_c of 0.5 km, b) Maximum reservoir extension L_c of 2.5 km, c) Maximum reservoir extension L_c of 4 km. Various reservoir ellipticities are considered: the black, blue, green and red curves are, respectively, for a prolate reservoir of ellipticity 0.5, a spherical reservoir, an oblate reservoir of ellipticity 2 and an oblate reservoir of ellipticity 4. The dashed blue curves are analytical results obtained by Pinel and Jaupart [2005] for the 2D plane strain case considering a cylindrical magma reservoir. Parts of the curves where the fault linking the Earth's surface rupture location to the reservoir walls is nearly vertical (dip larger than 80 degrees), are surrounded by a grey halo. Black circles are for the numerical simulations performed.

Figure 3. Caldera versus edifice radius as a function of the roof aspect ratio. Two different reservoir ellipticities are considered: the blue and red curves are, respectively, for a spherical reservoir and an oblate reservoir of ellipticity 4. Results are presented for various reservoir sizes: Dotted curves for a maximum reservoir extension L_c of 0.5 km, dashed curves for a maximum reservoir extension L_c of 2.5 km and plain curves for a maximum reservoir extension L_c of 4 km. Poisson's ratio is equal to 0.25 and the rock tensile strength is equal to 200 bars. Volcanic edifice density is 2800 kgm⁻³. Circles are for the numerical simulations performed. a) The edifice considered is a strato-volcano of slope $\alpha = 0.6$ and maximum allowed size 10 km. b) The edifice considered is a strato-volcano of slope $\alpha = 0.3$ and maximum allowed size 20 km. Characteristics of two strato-volcanoes with a slope close to 0.3, are reported (brown areas): Mount Mazama (caldera/edifice radius close to 0.4 and roof aspect ratio between 0.5 and 1, from [Pinel and Jaupart, 2005] and the CCDB) and Vesuvius (caldera/edifice radius close to 0.5 and roof aspect ratio between 0.6 and 1.2, caldera geometry is taken from the CCDB and edifice geometry is estimated from the SRTM Digital Elevation Model). c) The edifice considered is a shield volcano of slope $\alpha = 0.1$ and maximum allowed size 60 km. Characteristics of five shield volcanoes (edifice slope around 0.1) are reported (brown areas): Medecine Lake (caldera/edifice radius close to 0.17), Newberry (caldera/edifice radius close to 0.15), Ksudach, Krasheninnikov and Opala (caldera/edifice radius close to 0.33). Caldera geometry is taken from the CCDB and edifice geometry is estimated from the SRTM Digital Elevation Model.